

GH35GM Series

Part No.	Cross Ref. No.	Rated Voltage (VDC)	Operating Range (VDC)	@ Maximum Efficiency			Gear Ratio	Gear Case Size Dia. x Length (in.)	Motor Size Dia. x Depth (in.)	Shaft Size Dia. x Length (in.)	Pricing		
				Current (mA)	Speed (RPM)	Torque (g-cm)					1	10	50
155012	GH12-1926 	12	4.5 – 12	250	2	6000	3000:1	1.3 x 0.9	1.5 x 1.1	.23 x .90	\$ 21.95	\$ 19.79	\$ 17.79
155821	GH12-1830Y-P 	12	4.5 – 12	220	4.5	4500	1000:1	1.3 x 0.9	1.5 x 1.0	.23 x .90	22.89	20.63	18.54
155839	GH12-1641T-L 	12	3.0 – 12	250	20	3000	270:1	1.3 x 0.9	1.5 x 0.8	.23 x .90	25.95	23.95	21.45
152911	GH12-1926Y 	12	4.5 – 12	172	35	2370	100:1	1.3 x 1.0	1.5 x 0.7	.24 x .90	24.95	22.95	20.95
151441	GH12-1632TI 	12	4.5 – 12	275	57	2200	100:1	1.3 x 0.9	1.5 x 0.7	.23 x .90	21.95	18.55	16.69
155855	GH12-1641T-F 	12	3.0 – 12	250	71	1000	60:1	1.3 x 0.9	1.4 x 0.9	.23 x .90	24.75	22.30	20.00
155863	GH12-1926Y-F 	12	4.5 – 12	300	70	1000	60:1	1.3 x 0.9	1.4 x 0.9	.23 x .90	24.95	21.95	17.95
161374	GH12-1345T 	12	4.5 – 12	185	116	650	30:1	1.3 x 0.9	1.5 x 0.7	.23 x .90	23.95	21.59	19.45
161382	GH12-1634T 	12	4.5 – 12	295	145	850	30:1	1.3 x 0.9	1.4 x 0.7	.23 x .90	21.95	19.79	17.79
164786	GH12-1640Y 	12	4.5 – 24	120	220	180	10:1	1.3 x 0.9	1.4 x 0.7	.23 x .90	28.95	26.95	19.95
176030	GH24-1640Y00 	24	12 – 24	340	1.0	6000	3000:1	1.3 x 0.9	1.5 x 1.1	.23 x .90	21.95	18.64	16.35
176032	GH24-1640Y06 	24	12 – 24	340	50	2000	90:1	1.3 x 0.9	1.4 x 0.7	.23 x .90	24.95	21.95	15.95
176023	GH24-1640Y19 	24	12 – 24	340	148	1000	30:1	1.3 x 0.9	1.4 x 0.7	.23 x .90	28.49	25.59	22.99